



## COSEC PANEL LITE V2

### Standalone Mode Access Control for Single Location

#### General

Maximum Door Controllers	255
Users	25,000
Event Buffer	5,00,000

#### Communication

Interface	Ethernet or RS-485
Door Controllers on Ethernet	255
Door Controllers on RS-485	32

#### Operation Modes

Standalone Mode	Use Built-in GUI to Control Matrix Door Controllers and Users
Network Mode	Use for Feature and Capacity Enhancement for Access Control and Connected with COSEC CENTRA

#### Software

Built in Interface in a Standalone mode with Matrix Door Controllers

#### In/Out Ports

AUX-In Port	Yes, One Port Available
AUX-Out Port	Form C SPDT Relay output, max 5A@24 VDC or 5A@230VAC

#### Audio-Visual

LED	Available for Power, Status and Alarm
Buzzer	Yes

#### Electrical

Input Power	External Power Adaptor (12VDC/2A)
-------------	-----------------------------------

#### Physical

Mounting	Wall or Table Top
Dimensions (WxHxD)	79x105x27 mm
Weight	0.138 kgs, 0.304 Lbs

#### Environmental

Humidity	5% to 95 % RH Non-Condensing
Operating Temperature	-10 <sup>0</sup> C to +55 <sup>0</sup> C



**NUTECH SOLUTIONS**  
[www.nutechsolution.com](http://www.nutechsolution.com)